

Grease & Waste



-  breaks down & reduces organic waste
-  attacks source of odour
-  prevents drain clogging
-  non-toxic & non-corrosive
-  100% safe for humans, pets, & the planet

Ingredients: Proprietary enzyme formula, coconut and vegetable based surfactants, natural scent, water.

Packaging: 5L bottle - Ready to use

Min. Order Quantity: 4 x 5L bottles.

MSDS available upon request.

Manufactured in Australia.

ecosenses[®] Grease & Waste Digestor is formulated with our unique plant-based Enzyme Technology, delivering long-lasting cleaning action. It breaks down and eliminate grease and organic build up, maintaining clean and odour-free drains and grease traps.

Benefits to you:

-  Breaks down grease and waste without corroding pipes and grease traps
-  Natural ingredients makes it safe for regular use
-  Eliminates foul odour
-  Maintains health of pipes, drains, and grease traps
-  Improved alternative to traditional chemical degreaser

ecosenses[®] solutions are made from natural ingredients and are specially formulated to be safe for children, pets, and our planet.

-  **pH-neutral** solutions that will not damage surfaces and delicate fabrics
-  **100% biodegradable**, thus more environmentally sustainable
-  **Non-toxic, no alcohol, and hypoallergenic** for additional safety

AN INNOVATION BY **ecosoft^T**



US Environmental Protection Agency – Design for the Environment The DfE label means a product is safer for people and the environment. The US EPA Design for the Environment (DfE) label is awarded to products that do not pollute air or waterways, do not add harmful chemicals to the land, and are safer for fish and other aquatic life.

Suitable for

- Drains
- Floor traps
- Grease traps

Directions for use in drains and floor traps

1. **For drain treatment**, pour 120ml of solution into the drain, coating the sides of the drainpipe. Repeat for 14 days or as directed.
2. **For drain maintenance**, pour 120ml of solution into the drain, coating the sides of the drainpipe. Repeat for 2 times a week or as directed. Do not rinse with water.

Directions for use in grease traps

For grease trap treatment, after pumping out grease, pour solution directly into grease trap at a rate of 120ml per 370L of grease trap capacity. Dose every 3 days or as directed.

Try **ecosenses**  full range of Housekeeping, Air, and Professional Solutions for a healthier indoor environment. Contact us at jessica.cheong@ecosoftt.org or +65 9061 4116 for a trial now.

HOUSEKEEPING



AIR



PROFESSIONAL

